

OCR
A Level
Computer
Science
H446 – Paper 1



**Problem
recognition**

Unit 10
Computational
thinking



PG ONLINE

Objectives

- Learn about and apply the following to solve problems
 - Visualisation
 - Backtracking
 - Data mining
 - Heuristics
 - Performance modelling
 - Pipelining

Writing algorithms

- One of the oldest known algorithms was written by Euclid over 2000 years ago
- It's designed to find the greatest common divisor of two numbers (the largest number which divides both of them)



EUCLIDES

The GCD algorithm

- Suppose x and y represent two whole numbers
- Euclid's algorithm goes like this:

```
r = 1
WHILE r <> 0
    r = x mod y
    x = y
    y = r
ENDWHILE
OUTPUT y
```


- A flowchart is a **visualisation** of an algorithm
 - Draw a flowchart of this algorithm



The GCD algorithm

```
r = 1
WHILE r <> 0
    r = x mod y
    x = y
    y = r
ENDWHILE
OUTPUT x
```

- Test the algorithm by tracing the values of r , x and y starting with $x = 420$, $y = 66$



The GCD algorithm

```
r = 1
WHILE r <> 0
    r = x mod y
    x = y
    y = r
ENDWHILE
OUTPUT x
```

- Test the algorithm by tracing the values of r , x and y starting with $x = 420$, $y = 66$
 - Output is 6

r	x	y
1	420	66
24	66	24
18	24	18
6	18	6
0	6	0

Visualising an algorithm


- An image is much easier for a human to understand than a table of numbers
- What does the graph represented below look like?

	A	B	C	D	E	F	G	H
A		1 5	1 3	2 0				
B	1 5				1 8			
C	1 3						1 4	
D	2 0				1 7		8	
E		1 8		1 7		1 6		
F					1 6			7
G			1 4	8				1 0
H							1	



The graph


- Here it is visualised as a set of nodes and edges



- The weights on the edges could be distances or costs


Shortest path algorithm

- Suppose we wanted to find the shortest path from city A to city D
- One method would be to perform an **exhaustive search** of all possible routes
- With 4 cities, how many possible routes are there?
 - What is the shortest route?




Exhaustive search

- With 4 cities, there are $3 \times 2 = 6$ possible routes
- With 5 cities, there are $4 \times 3 \times 2$ routes
- The shortest route from A to D is A → B → C → D, a distance of 21
- With only 4 cities, an exhaustive search is possible
 - But what if there are 8 cities?



Exhaustive search

- The formula for the number of possible routes for 8 cities is:
 $7! = 7 \times 6 \times 5 \times 4 \times 3 \times 2 \times 1 = 211,680$
- The number of possible routes for 10 cities is $10! = 3,628,800$
- Clearly a better algorithm needs to be found
 - We'll use an algorithm to find the shortest distance from A to D



Backtracking

- One technique is **backtracking**, whereby you go some way along one route and then backtrack to see if there is a better route


- Starting at A, visit B, C and D to see which is the shortest distance
- B is shortest, so backtrack to A, travel to B and from there visit C and D

$$A \rightarrow B \rightarrow C \text{ is } 5 + 10 = 15$$

$$A \rightarrow B \rightarrow D \text{ is } 5 + 18 = 23$$



- The shortest path so far is $A \rightarrow B \rightarrow C = 15$
- Backtrack to C. $A \rightarrow B \rightarrow C \rightarrow D = 15 + 6 =$

21



Solving mazes

- A maze can be represented as a graph
- A depth-first traversal is used to explore a path until a dead-end is reached, and then it backtracks to the previous node, and tries the next path



Worksheet 6

- Try the first question in **Task 1** of Worksheet 6
 - If you have time, try the second one too



Can it be solved?

- Sometimes it is not possible to find a solution to a problem in a reasonable time
- Cracking a strong password may be impossible using an exhaustive search



Cracking a password

- What other methods, apart from an exhaustive search taking 34 thousand years, could you try to discover someone's password or crack a code?

Educated guess?

- To crack a password, you could try guesswork based on the person's family, names, birthdates, favourite team, etc.
- You could try comparing it with words in a dictionary
- To crack a code, if you had a large chunk of encrypted text, you could use a frequency analysis of letters – for example 'e' is the commonest letter in English, followed by 't'


Heuristic methods

- Heuristic methods include ‘rules of thumb’, educated guesses, intuitive judgements or common sense
- Teachers, students, psychologists, chess players, use heuristics to solve problems
 - How often do you use a heuristic approach to a problem? Think of examples



An intractable problem

- The Travelling Salesman Problem (TSP) is a problem which cannot be completely solved
- The problem is to find the shortest route which visits every city and returns to the start



Heuristic methods

- A heuristic method is used to rapidly find a solution that is 'good enough', even though it might not be the optimal solution
- Many algorithms have been invented to provide a heuristic solution to the Travelling Salesman Problem (TSP)
 - The best heuristic solutions are within 2-3% of the optimal solution for up to 85,000 cities or nodes

Applications of heuristic methods

- The heuristic approach is used in many applications such as
 - routing messages across the Internet
 - building circuit boards
 - transportation
 - virus checking
 - DNA analysis
 - artificial intelligence



Data mining

- Data mining is the process of collecting and then analysing huge amounts of data
- Many organisations such as the National Health Service, police, Google, Amazon and supermarkets collect billions of bytes of data about people
- They can then analyse or ‘mine’ the data to find connections and associations
- A range of modelling techniques are used to help to identify patterns in the data

Applications of data mining


- Increasing response rates to marketing campaigns by being able to target them more accurately to the needs of each customer
- Anticipating resource demands
- Detecting fraud and cybersecurity issues
- Finding connections between seemingly unconnected events

Big data

- The term **big data** is often used in connection with data mining
- It implies that huge amounts of data are collected and stored
- It is defined by three major features, known as the 3Vs: **Volume**, **Variety** and **Velocity**
- **Parallel computing**, in which algorithm tasks are executed **concurrently** on a cluster of machines or supercomputers, is fundamental to managing big data tasks

Mining supermarket data

- A supermarket can customise their advertising and special offers, depending on your purchase history or that of other customers who




Amazon data mining

- Amazon make recommendations based on what other readers who have read the same books as you have also read



Medical applications of data mining

- Data mining and big data techniques are widely used in the public health field, discovering new patterns among population groups using social media data



Performance modelling

- How efficient is your algorithm?
- One measure of efficiency is the Big-O notation (covered in Section 12)
- This measures the suitability of algorithms in terms of execution time and space
- You can time different algorithms using built-in timer functions
 - The performance of some algorithms deteriorates so rapidly as the problem size increases that they are not usable

Performance of sorting algorithms

- Sorting algorithms vary enormously in their efficiency
- The bubble sort is the slowest of the well-known algorithms
- The quicksort is very fast for a large number of items

Worksheet 2

- Now try **Task 2** in the worksheet



Pipelining

- Pipelining is an implementation technique where multiple instructions are overlapped in execution
- Instructions enter the 'pipeline' at one end, and at each stage part of the instruction is completed and moves to the next stage while another instruction enters the pipeline – rather like an assembly line

Pipelining in PCs

- Pipelining is now commonplace in PCs
- Intel chips can execute many instructions simultaneously to achieve high processing speeds of 3GHz and more

Plenary

- You should be able to explain and give examples of
 - visualisation
 - backtracking
 - heuristics
 - data mining
 - performance modelling
 - pipelining

and say how they are used in solving problems

Copyright

© 2016 PG Online Limited

The contents of this unit are protected by copyright.

This unit and all the worksheets, PowerPoint presentations, teaching guides and other associated files distributed with it are supplied to you by PG Online Limited under licence and may be used and copied by you only in accordance with the terms of the licence. Except as expressly permitted by the licence, no part of the materials distributed with this unit may be used, reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic or otherwise, without the prior written permission of PG Online Limited.

Licence agreement

This is a legal agreement between you, the end user, and PG Online Limited. This unit and all the worksheets, PowerPoint presentations, teaching guides and other associated files distributed with it is licensed, not sold, to you by PG Online Limited for use under the terms of the licence.

The materials distributed with this unit may be freely copied and used by members of a single institution on a single site only. You are not permitted to share in any way any of the materials or part of the materials with any third party, including users on another site or individuals who are members of a separate institution. You acknowledge that the materials must remain with you, the licencing institution, and no part of the materials may be transferred to another institution. You also agree not to procure, authorise, encourage, facilitate or enable any third party to reproduce these materials in whole or in part without the prior permission of PG Online Limited.

